

**N-沟道功率 MOS 管/ N-CHANNEL POWER MOSFET**


**SIF9N20A**

- 特点：导通电阻低 开关速度快 输入阻抗高 符合RoHS规范
- FEATURES: ■LOW ON-RESISTANCE ■FAST SWITCHING ■HIGH INPUT RESISTANCE ■RoHS COMPLIANT
- 应用：照明 不间断电源 开关电源 AC-DC 转换电路
- APPLICATION: ■LIGHTING ■UNINTERRUPTED POWER SUPPLY ■SWITCH MODE POWER SUPPLY  
■ AC-DC CONVERSION CIRCUIT

●最大额定值 (Tc=25°C)

●Absolute Maximum Ratings (Tc=25°C) TO-220/220FP

参数 PARAMETER	符号 SYMBOL	额定值 VALUE	单位 UNIT
漏-源电压 Drain-source Voltage	V <sub>DS</sub>	200	V
栅-源电压 gate-source Voltage	V <sub>GS</sub>	±30	V
漏极电流 Continuous Drain Current TC=25°C	I <sub>D</sub>	9	A
漏极电流 Continuous Drain Current TC=100°C	I <sub>D</sub>	4.5	A
最大脉冲电流 Drain Current — Pulsed ①	I <sub>DM</sub>	36	A
耗散功率 Power Dissipation	P <sub>tot</sub>	TO-220:82	W
		TO-220FP:38.5	
最高结温 Junction Temperature	T <sub>J</sub>	150	°C
存储温度 Storage Temperature	T <sub>STG</sub>	-55-150	°C
单脉冲雪崩能量 Single Pulse Avalanche Energy ②	E <sub>AS</sub>	142	mJ



●电特性 (Tc=25°C)

●Electronic Characteristics (Tc=25°C)

参数 PARAMETER	符号 SYMBOL	测试条件 TEST CONDITION	最小值 MIN	典型值 TYP	最大值 MAX	单位 UNIT
漏-源击穿电压 Drain-source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	200			V
击穿电压温度系数 Breakdown Voltage Temperature Coefficient	ΔBV <sub>DSS</sub> / ΔT <sub>J</sub>	I <sub>D</sub> =250uA, Referenced to 25°C		0.2		V/°C
栅极开启电压 Gate Threshold Voltage	V <sub>GS(TH)</sub>	V <sub>GS</sub> =V <sub>DS</sub> , I <sub>D</sub> =250μA	2.5		3.5	V
漏-源漏电流 Drain-source Leakage Current	I <sub>DSS</sub>	V <sub>DS</sub> =200V, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C			1	μA
		V <sub>DS</sub> =200V, V <sub>GS</sub> =0V, T <sub>J</sub> =125°C			10	μA
跨导 Forward Transconductance	G <sub>FS</sub>	V <sub>DS</sub> =10V, I <sub>D</sub> =4.5A ③	5.0			S

●订单信息/ORDERING INFORMATION:

包装形式/PACKING	订货编码/ORDERING CODE	
	普通塑封料/ Normal Package Material	无卤塑封料/Halogen Free
TO-220 条管装/TUBE PACKING	SIF9N20A TO-220-TU	SIF9N20A TO-220-TU-HF
TO-220FP 条管装/TUBE PACKING	SIF9N20A TO-220FP-TU	SIF9N20A TO-220FP-TU-HF

**N-沟道功率 MOS 管/ N-CHANNEL POWER MOSFET**

**SIF9N20A**

参数 PARAMETER	符号 SYMBOL	测试条件 TEST CONDITION	最小值 MIN	典型值 TYP	最大值 MAX	单位 UNIT
栅极漏电流 Gate-body Leakage Current ( $V_{DS} = 0$ )	$I_{GSS}$	$V_{GS} = \pm 30V$			$\pm 100$	nA
漏-源导通电阻 Static Drain-source On Resistance	$R_{DS(ON)}$	$V_{GS} = 10V, I_D = 4.5A$ ③		0.22	0.30	$\Omega$
输入电容 Input Capacitance	$C_{iss}$	$V_{GS} = 0V, V_{DS} = 25V$ $F = 1.0MHz$		565		pF
输出电容 Output Capacitance	$C_{oss}$			86		pF
米勒电容 Miller Capacitance	$C_{rss}$			25		pF
关断延迟 Turn -Off Delay Time	$T_d(off)$	$V_{DD} = 100V, I_D = 5.4A$ $R_G = 3.5\Omega, R_D = 25\Omega$ ③		8.1		ns
关断延迟 Turn -Off Delay Time	$T_d(off)$			27		ns
栅极电荷 Total Gate Charge	$Q_g$	$I_D = 5.4A, V_{DS} = 160V$ $V_{GS} = 10V$ ③		16.5		nC
栅源电荷 Gate-to-Source Charge	$Q_{gs}$			2.4		nC
栅漏电荷 Gate-to-Drain Charge	$Q_{gd}$			3.9		nC
二极管正向电流 Continuous Diode Forward Current	$I_S$				9.0	A
二极管正向压降 Diode Forward Voltage	$V_{SD}$	$T_j = 25^\circ C, I_S = 9A$ $V_{GS} = 0V$ ③			1.45	V
反向恢复时间 Reverse Recovery Time	$t_{rr}$	$T_j = 25^\circ C, I_f = 9A$ $di/dt = 100A/\mu s$ ③		120	176	ns
反向恢复电荷 Reverse Recovery Charge	$Q_{rr}$			542	815	$\mu C$

●热特性

●Thermal Characteristics

参数 PARAMETER	符号 SYMBOL	最大值 MAX		单位 UNIT
		TO-220	TO-220FP	
热阻结-壳 Thermal Resistance Junction-case	$R_{thJC}$	1.52	3.25	$^\circ C/W$
热阻结-环境 Thermal Resistance Junction-ambient	$R_{thJA}$	62.5	62.5	$^\circ C/W$

注释(Notes):

- ① 脉冲宽度：以最高结温为限制  
Repetitive rating: Pulse width limited by maximum junction temperature
- ② 初始结温= $25^\circ C$ ,  $V_{DD} = 50V$ ,  $L = 3.5 mH$ ,  $R_G = 25\Omega$ ,  $I_{AS} = 9.0A$   
Starting  $T_j = 25^\circ C$ ,  $V_{DD} = 50V$ ,  $L = 3.5 mH$ ,  $R_G = 25\Omega$ ,  $I_{AS} = 9.0A$
- ③ 脉冲测试：脉冲宽度 $\leq 300\mu s$ ，占空比 $\leq 2\%$   
Pulse Test : Pulse width  $\leq 300\mu s$ , Duty cycle  $\leq 2\%$

N-沟道功率 MOS 管/ N-CHANNEL POWER MOSFET

SIF9N20A

● 特性曲线




图 1 输出特性曲线,  $T_C=25^\circ\text{C}$

Fig1 Typical Output Characteristics,  $T_C=25^\circ\text{C}$




图 2 导通电阻与漏极电流和栅极电压曲线

Fig2 On-Resistance Vs. Drain Current and Gate Voltage




图 3 导通电阻与温度曲线

Fig3 Normalized On-Resistance Vs. Temperature




图 4 二极管正向电压曲线

Fig4 Typical Source-Drain Diode Forward Voltage




图 5 最大漏极电流与壳温曲线

Fig5 Maximum Drain Current Vs. Case Temperature





图 6 最大安全工作区曲线

Fig6 Maximum Safe Operating Area

## TO-220 封装机械尺寸 TO-220 MECHANICAL DATA

单位：毫米/UNIT: mm

符号 SYMBOL	最小值 min	典型值 nom	最大值 max	符号 SYMBOL	最小值 min	典型值 nom	最大值 max
A	4.00		4.80	E	9.90		10.70
B	1.20		1.50	e		2.54	
B1	1.00		1.40	F	1.10		1.45
b1	0.65		1.00	L	12.50		14.50
c	0.35		0.75	L1	3.00	3.50	4.00
D	15.00		16.50	Q	2.50		3.00
D1	5.90		6.90	Q1	2.00		3.00
				φP	<b>3.50</b>		3.90



## TO-220FP 封装机械尺寸 TO-220FP MECHANICAL DATA

单位:毫米/UNIT: mm

符号 SYMBOL	最小值 min	典型值 nom	最大值 max	符号 SYMBOL	最小值 min	典型值 nom	最大值 max
A	4.40		4.95	E	9.60		10.30
A <sub>1</sub>	2.30		2.90	e		2.54	
<b>b</b>	<b>0.70</b>		<b>0.90</b>	<b>L</b>	<b>12.40</b>		<b>14.00</b>
b <sub>1</sub>	<b>1.18</b>		<b>1.45</b>	<b>L<sub>2</sub></b>	<b>2.30</b>		<b>2.60</b>
<b>c</b>	<b>0.40</b>		<b>0.70</b>	L <sub>3</sub>	3.00		4.00
D	14.50		17.00	øp	3.00		3.50
D1	6.10		9.00	Q	2.30		2.80

